



SAFETY DATA SHEET

1. Identification

Product identifier	SHEETROCK® Brand Acoustical Sealant
Other means of identification	
SDS number	61000040001
Synonyms	Sound Blocking Sealant
Recommended use	Interior use.
Recommended restrictions	Use in accordance with manufacturer's recommendations.

Manufacturer/Importer/Supplier/Distributor information

Company name	United States Gypsum Company
Address	550 West Adams Street Chicago, Illinois 60661-3637
Telephone	1-800-874-4968
Website	www.usg.com
Emergency phone number	1-800-507-8899

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1A
	Reproductive toxicity	Category 1B
	Specific target organ toxicity, repeated exposure	Category 2 (Kidneys)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 2
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	

Label elements



Signal word	Danger
Hazard statement	May cause cancer. Suspected of damaging fertility or the unborn child by inhalation. May cause damage to organs (Kidneys) through prolonged or repeated exposure. Toxic to aquatic life with long lasting effects.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment.
Response	If exposed or concerned: Get medical advice/attention. Collect spillage.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	> 55
Benzyl butyl phthalate	85-68-7	< 10
Ethylene glycol	107-21-1	< 5

Impurities

Chemical name	CAS number	%
Crystalline silica (Quartz)	14808-60-7	< 1

Composition comments All concentrations are in percent by weight unless ingredient is a gas.

4. First-aid measures

Inhalation	Dust irritates the respiratory system, and may cause coughing and difficulties in breathing. Move injured person into fresh air and keep person calm under observation. Get medical attention if symptoms persist.
Skin contact	Contact with dust: Rinse area with plenty of water. Get medical attention if irritation develops or persists.
Eye contact	Dust in the eyes: Do not rub eyes. Flush thoroughly with water. If irritation occurs, get medical assistance.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing. May cause allergic skin disorders in sensitive individuals.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved.

5. Fire-fighting measures

Suitable extinguishing media	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media	Not applicable.
Specific hazards arising from the chemical	Not a fire hazard.
Special protective equipment and precautions for firefighters	Selection of respiratory protection for firefighting: follow the general fire precautions indicated in the workplace. Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Use standard firefighting procedures and consider the hazards of other involved materials.
Specific methods	Cool material exposed to heat with water spray and remove it if no risk is involved.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	See Section 8 of the SDS for Personal Protective Equipment.
Methods and materials for containment and cleaning up	Large Spills: Scoop spilled materials and recover as much of the product as possible for use. If spillage is unrecoverable dispose according to local, state, and federal regulations. Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.
Environmental precautions	Avoid discharge to drains, sewers, and other water systems.

7. Handling and storage

Precautions for safe handling

Avoid inhalation of dust and contact with skin and eyes. Minimize dust generation and accumulation. In case of insufficient ventilation, wear suitable respiratory equipment. Observe good industrial hygiene practices. Use proper lifting techniques.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry, well-ventilated place. Store in a closed container away from incompatible materials. Protect from moisture. Keep away from heat. Do not use if material has spoiled, i.e., there is a moldy appearance or an unpleasant odor. Keep containers closed when not in use.

Filled 4.5 gallon pails of joint compound may be stacked a maximum of 3 layers high on a standard 48 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

Filled cartons of joint compound may be stacked a maximum of 3 layers high on a standard 42 x 42 or 42 x 48 pallet (16 pails per layer, 3 layers high). Pallets may only be stacked a maximum of two high.

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	PEL	5 mg/m ³ 15 mg/m ³	Respirable fraction. Total dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.3 mg/m ³ 0.1 mg/m ³	Total dust. Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Ethylene glycol (CAS 107-21-1)	Ceiling	100 mg/m ³	Aerosol.
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Limestone (CAS 1317-65-3)	TWA	5 mg/m ³ 10 mg/m ³	Respirable. Total
Impurities	Type	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Provide sufficient ventilation for operations causing dust formation. Observe occupational exposure limits and minimize the risk of exposure.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety goggles.

Skin protection

Hand protection

It is a good industrial hygiene practice to minimize skin contact. For prolonged or repeated skin contact use suitable protective gloves.

Other

Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use a NIOSH/MSHA approved air purifying respirator as needed to control exposure. Consult with respirator manufacturer to determine respirator selection, use, and limitations. Use positive pressure, air-supplied respirator for uncontrolled releases or when air purifying respirator limitations may be exceeded. Follow respirator protection program requirements (OSHA 1910.134 and ANSI Z88.2) for all respirator use.
Thermal hazards	None.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment separately from regular wash. Observe any medical surveillance requirements.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Paste.
Color	Off-white.
Odor	Acrylic.
Odor threshold	Not applicable.
pH	8 - 10
Melting point/freezing point	Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	1.6 (H ₂ O=1)
Solubility(ies)	
Solubility (water)	Miscible with water.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Bulk density	13.4 lb/gal
VOC (Weight %)	< 15 g/l

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	Hazardous polymerization does not occur.
Conditions to avoid	None known.
Incompatible materials	None known.

Hazardous decomposition products Above 1472°F (800°C) limestone (CaCO₃) can decompose to lime (CaO) and release carbon dioxide (CO₂).

11. Toxicological information

Information on likely routes of exposure

Inhalation Airborne dust may irritate throat and upper respiratory system causing coughing.
Skin contact May cause allergic skin reactions especially in individuals with pre-existing skin disease such as eczema. (See Section 16).
Eye contact Airborne dust may cause mechanical eye irritation.
Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Dust may irritate eyes and mucous membranes of the nose, throat and upper respiratory system causing sneezing and/or coughing.

Information on toxicological effects

Acute toxicity Not expected to be a hazard under normal conditions of intended use.

Components	Species	Test Results
Ethylene glycol (CAS 107-21-1)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	9530 mg/kg
<i>Oral</i>		
LD50	Rat	4700 mg/kg

Skin corrosion/irritation Prolonged or repeated skin contact may cause drying, cracking, or irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization The product contains a small amount of sensitizing substance which may provoke an allergic reaction among sensitive individuals after repeated contact. For detailed information, see section 16.

Germ cell mutagenicity Data does not suggest that this product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity May cause cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Benzyl butyl phthalate (CAS 85-68-7) 3 Not classifiable as to carcinogenicity to humans.
Crystalline silica (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility or the unborn child.

Specific target organ toxicity - single exposure No data available, but none expected.

Specific target organ toxicity - repeated exposure May cause damage to the following organs through prolonged or repeated exposure:

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects. For detailed information, see section 16.

12. Ecological information

Ecotoxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test Results
Ethylene glycol (CAS 107-21-1)		
Aquatic		
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 8050 mg/l, 96 hours

Persistence and degradability	No data available.
Bioaccumulative potential	Bioaccumulation is not expected.
Partition coefficient n-octanol / water (log Kow)	
Benzyl butyl phthalate (CAS 85-68-7)	4.91
Ethylene glycol (CAS 107-21-1)	-1.36
Mobility in soil	No data available.
Other adverse effects	None expected.

13. Disposal considerations

Disposal instructions	Dispose in accordance with applicable federal, state, and local regulations. Recycle responsibly.
Local disposal regulations	Dispose of in accordance with local regulations.
Hazardous waste code	Not regulated.
Waste from residues / unused products	Dispose of in accordance with local regulations.
Contaminated packaging	Dispose of in accordance with local regulations.

14. Transport information

DOT	
UN number	UN3077
UN proper shipping name	Environmentally hazardous substances, solid, n.o.s. (Benzyl butyl phthalate RQ = 1312 LBS)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
Special provisions	8, 146, 335, A112, B54, IB8, IP3, N20, T1, TP33
Packaging exceptions	155
Packaging non bulk	213
Packaging bulk	240
IATA	
UN number	UN3077
UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (Benzyl butyl phthalate)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	Yes
ERG Code	9L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.
IMDG	
UN number	UN3077
UN proper shipping name	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Benzyl butyl phthalate)
Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Packing group	III
Environmental hazards	
Marine pollutant	Yes
EmS	F-A, S-F
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

CERCLA Hazardous Substance List (40 CFR 302.4)

Benzyl butyl phthalate (CAS 85-68-7)	LISTED
Ethylene glycol (CAS 107-21-1)	LISTED

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - Yes
Fire Hazard - No
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical Yes

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Ethylene glycol	107-21-1	< 5

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylene glycol (CAS 107-21-1)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

US state regulations

US. Massachusetts RTK - Substance List

Benzyl butyl phthalate (CAS 85-68-7)
Crystalline silica (Quartz) (CAS 14808-60-7)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)

US. New Jersey Worker and Community Right-to-Know Act

Benzyl butyl phthalate (CAS 85-68-7)
Crystalline silica (Quartz) (CAS 14808-60-7)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Benzyl butyl phthalate (CAS 85-68-7)
Crystalline silica (Quartz) (CAS 14808-60-7)
Ethylene glycol (CAS 107-21-1)
Limestone (CAS 1317-65-3)

US. Rhode Island RTK

Benzyl butyl phthalate (CAS 85-68-7)
Ethylene glycol (CAS 107-21-1)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Benzyl butyl phthalate (CAS 85-68-7)

Crystalline silica (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 01-April-2015

Revision date -

Version # 01

Further information Skin Sensitization Potential: This product contains an amount of Triazinetriethanol (THT) (CAS No. 4719-04-4) that is below the approved EPA regulated limits. THT can act as a sensitizer. Numerous human studies with concentrations up to 1% yielded negative (no sensitization) results. However, some results showed positive reactions in concentrations <0.5% mostly in persons with eczema.

Crystalline silica: Raw materials in this product may contain respirable crystalline silica. Exposures to respirable crystalline silica are not expected during the normal use of this product. However, actual levels must be determined by workplace hygiene testing. Prolonged and repeated exposure to airborne free respirable crystalline silica can result in lung disease (i.e., silicosis) and/or lung cancer.

Bucket NFPA Classification:

Health: 0

Flammability: 1

Physical hazard: 0

NFPA Ratings:

Health: 2

Flammability: 0

Physical hazard: 0

Hazard Scale: 0 = Minimal 1 = Slight 2 = Moderate 3 = Serious 4 = Severe

HMIS® ratings

Health: 1*

Flammability: 0

Physical hazard: 0

NFPA ratings



List of abbreviations

NFPA: National Fire Protection Association.

References

Registry of Toxic Effects of Chemical Substances (RTECS)

HSDB® - Hazardous Substances Data Bank

Torben et al. (2001). Environmental and Health Assessment of Substances in Household Detergents and Cosmetic Products.

Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.