

SINCLAIR PAINT CO -- AQUA SASH ULTRA DEEP BASE, BLUE, 4846 -- 8010-00N077623

===== Product Identification =====

Product ID:AQUA SASH ULTRA DEEP BASE, BLUE, 4846

MSDS Date:02/26/1992

FSC:8010

NIIN:00N077623

MSDS Number: CDTSY

=== Responsible Party ===

Company Name:SINCLAIR PAINT CO

Address:6100 SOUTH GARFIELD AVE

City:LOS ANGELES

State:CA

ZIP:90040

Country:US

Info Phone Num:213-888-8888

Emergency Phone Num:213-664-2121

Preparer's Name:J G PRINZ

CAGE:0U0K0

=== Contractor Identification ===

Company Name:SINCLAIR PAINT COMPANY

Address:6100 S. GARFIELD AVE

Box:City:LOS ANGELES

State:CA

ZIP:90040

Country:US

Phone:213-888-8888

CAGE:0U0K0

===== Composition/Information on Ingredients =====

Ingred Name:1,2-PROPANEDIOL; (PROPYLENE GLYCOL). VP:0.2 68F

CAS:57-55-6

RTECS #:TY2000000

Fraction by Wt: 10%

OSHA PEL:N/K

ACGIH TLV:N/K

Ingred Name:2-PROPANOL, 1-METHOXY-; (PROPYLENE GLYCOL MONOMETHYL
ETHER). VP:10.9 @ 77F

CAS:107-98-2

RTECS #:UB7700000

Fraction by Wt: 1%

OSHA PEL:100 PPM

ACGIH TLV:100 PPM/150STEL

Ingred Name:COATING VOLATILE ORGANIC COMPOUND:2.06 LB/GL (247 G/L).

MATERIAL VOLATILE ORGANIC COMPOUND:0.99 LB/GL (118 G/L)

RTECS #:9999999VO

OSHA PEL:N/K

ACGIH TLV:N/K

===== Hazards Identification =====

LD50 LC50 Mixture:NONE SPECIFIED BY MANUFACTURER.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:MAY CAUSE IRRIT TO SKIN, EYES, &
INTESTINAL SYS. SYMPS OF EXPOS:INHAL:ADVERSE HLTH EFTS FROM
VAPS/SPRAY MISTS IN POORLY VENTILATED AREAS MAY INCLUDE IRRIT OF
MUC MEMB OF NOSE, THROAT, & RESP TRA CT & SYMPS OF HCH & NAUS.
EYES:INDIRECTCONT MAY CAUSE IRRIT. SKIN:PRLNGD/RPTD CONT W/PROD MAY

CAUSE (EFTS OF OVEREXP)

Explanation of Carcinogenicity:NOT RELEVANT.

Effects of Overexposure:HLTH HAZ:IRRIT. SKIN ABSORP:REDNESS,
 DRYING/OTHER SIGNS OF IRRIT/CONT DERM. INGEST:CAN CAUSE GI IRRIT,
 NAUS, VOMIT, & DIARR. CHRONIC:NONE KNOWN.

Medical Cond Aggravated by Exposure:NONE.

===== First Aid Measures =====

First Aid:SKIN:CLEANSE THOROUGHLY W/SOAP & WATER. REMOVE ALL CONTAMD
 CLTHG. EYES:FLUSH IMMED W/LG AMTS OF WATER FOR @ LST 15 MINS. TAKE
 TO PHYS FOR MED ATTN. INHAL:REMOVE TO FRESH AIR. INGEST:DRINK 1-8
 GLASSES OF WATER TO DILUTE. DO NOT INDUCE VOMIT. CONSULT
 PHYS/POISON CONTROL CENTER IMMED. TREAT SYMPTOMATICALLY.

===== Fire Fighting Measures =====

Lower Limits:1.6%

Upper Limits:13.8%

Extinguishing Media:FOAM, CO*2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures:USE NIOSH APPROVED SCBA & FULL PROTECTIVE
 EQUIPMENT . THIS IS A WATER-BASED COATING. WILL NOT SUPPORT
 COMBUSTION.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HIGH
 TEMPERATURES MAY EXPLODE OR BURST DUE TO BUILD UP OF STEAM
 PRESSURE.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE, CONTAIN/ABSORB WITH INERT MATL (I.E.,
 SAND, VERMICULATE, ETC.). TRANSFER TO CONTAINERS FOR RECOVERY OR
 DISPOSAL. PREVENT RUNOFF INTO SEWERS, STREAMS, OR OTHER BODIES OF
 WATER.

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT EXPOSE TO EXTREMES IN
 TEMPERATURES. AVOID EXPOSURE TO HIGH TEMPERATURES. DO NOT ALLOW TO
 FREEZE.

Other Precautions:DO NOT TAKE INTERNALLY. AVOID PROLONGED OR REPEATED
 EXPOSURE TO LEVELS ABOVE TLV.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED USE
 NIOSH APPROVED ORGANIC VAPOR AND MIST PROTECTION.

Ventilation:USE ADEQUATE MECHANICAL (GENERAL AND/OR LOCAL) VENTILATION
 TO MAINTAIN EXPOSURE BELOW TLV.

Protective Gloves:RESIST SUCH AS POLYETHYLENE GLOVES.

Eye Protection:ANSI APPRVD CHEM WORKERS GOGGLES .

Other Protective Equipment:ANSI APPRVD EYE WASH & DELUGE SHOWER . WEAR
 IMPERVIOUS CLOTHING.

Work Hygienic Practices:WASH HANDS BEFORE EATING OR USING RESTROOM.
 REMOVE AND WASH CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health
 NONE SPECIFIED BY MANUFACTURER.

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:SEE INGS

Vapor Density:LTR/AIR

Spec Gravity:1.1 (H*20=1)
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:COMPLETELY
Appearance and Odor:TYPICAL FOR WATER BASED LATEX COATING.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONTACT WITH STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:NONE.
Hazardous Decomposition Products:MAY FORM TOXIC MATERIALS, CARBON
DIOXIDE, CARBON MONOXIDE, ETC.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE,
OR FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.